

Skedco, Inc.

Web Site: <http://www.skedco.com> • E-mail: skedco@skedco.com

*P.O. Box 3390 • Tualatin, Oregon 97062 USA Oregon 97062 USA
Phone (503) 691-7909 • FAX (503) 691-7973*

SKED-EVAC TRIPOD FACT SHEET

- Adjustable from 183cm to 305 cm at the anchors
- Proof loaded to 2400 kg @ 305cm
- Proof loaded to 4300 kg @ 244cm
- SWC chart permanently affixed to tripod
- Adjustable in 12.7cm increments
- Made of aircraft quality aluminum and stainless steel only
- Adjustments attached with plastic coated stainless steel lanyard to prevent loss
- Feet adjust for flat hard surfaces to soft uneven surfaces
- Holes in feet to stake or bolt tripod permanently in place
- 3 anchors anodized in red color
- Anchors will accept up to 4 large carabiners
- Cast aluminum head limits amount of spread of legs
- All bolts are permanently locked in place
- Legs are easily adjustable
- Bolts through head, anchors and upper legs are 1.25cm diameter x 11.5cm long with heavy nuts
- Bolts through feet and lower leg are 1cm x 9cm long using self locking nuts and Mil-Spec flat washers
- Hitch pins are 1cm diameter x 8cm long with plastic coated 1/16" cable lanyard and "hairpin" cotter pin
- All of the bolts, nuts and washers used assemble with the tripod are stainless steel
- Anchors, head, legs and feet are 6061 T-6 aluminum